



DIGITAL ELECTRONIC WRENCHES DRILCO



Easy Touse – Menu Driven

Accuracy better than 1%

Viewing angle 170%

Battery life up to 180 hours

Option to customise

Jean Louis MENEGON

Représentant et Conseiller

Région Sud Ouest

Tel : 06 76 08 96 83

Email: jlouismenegon@aol.com

www.menegon-metrologie.com

	EZ	PRO	SUPER	PAR/ANG
Menu options				
- Language, Comms, Peak, Set, Recall, Upload, Clear	NO	YES	YES	YES
- Date, Track, Preset, Units	YES	YES	YES	YES
- Display: Large organic LED	YES	YES	YES	YES
- Units: cNm, Nm, mKg, cmKg, ozins, lbins, lbft	YES	YES	YES	YES
- Alarms: Audible & Visual signals	YES	YES	YES	YES
- Automatic zero point setting	YES	YES	YES	YES
- Automatic power down	YES	YES	YES	YES
- Over-torque: Warning system on display	YES	YES	YES	YES
- Interchangeable heads	YES	YES	YES	YES
- Batteries: Lifespan 180 hours	YES	YES	YES	YES
- Storage capacity: 2000+	NO	YES	YES	YES
- Languages: English, Chinese, French, German, Italian, Japanese, Polish, Portuguese, Spanish, Russian, others on request	Just English	YES	YES	YES
- Programmable presets: 99, via PC or directly on wrench	NO	NO	YES	YES
- Electronic calibration: by date or Lumber of measurements	NO	NO	YES	YES
- Accuracy: better than 1% of actual Redding LHS & RHS from 10% to 1100% of specified range	YES	YES	YES	YES
- Display of measurements: start from 2% of maximum	YES	YES	YES	YES
- Window Excel & SPC compatible	NO	NO	YES	YES
- Comms: USB bi-directional communications	NO	YES	YES	YES
- PLC Communications: using ASCII or binary transfer	NO	NO	YES	YES

Note: Wrench can be configured to client specification

TORQUE/ANGLE WRENCHES:

- Torque & angle function
- Shows torque applied & preset, just move angle (default 3°) and the final torque /angle results



Displays Actual Torque as applied



Screen changes colour as preset Torque reached



Store & View 2000+ results or upload to PC & SPC




4 AA batteries

Robust bi-directional ratchet head

Large colour organic LED screen high visibility warning signals

Membrane tactile switch with green/red LED warning signals
















EZ	PRO	SUPER	TORQUE/ANG	Drive / Adaptor	Nm	InLbs	Ftlbs	Length (mm)	Weight (kg)
LDTE010	LDTP010	LDTS010	LDTA010	1/4" 3/8": 9x12	1-10	8.8-88	.73-7.3	410	.85
LDTE020	LDTP020	LDTS020	LDTA020	1/4" 3/8": 9x12	2-20	17-177	1.4-14	410	.85
LDTE050	LDTP050	LDTS050	LDTA050	1/4" 3/8": 9x12	5-50	44-442	3.6-36	410	.85
LDTE100	LDTP100	LDTS100	LDTA100	1/4" 3/8": 9x12	10-100	88-885	7.3-73	410	.85
LDTE135	LDTP135	LDTS135	LDTA135	1/4" 3/8": 9x12	13.5-135	---	9.9-99	410	.85
LDTE150	LDTP150	LDTS150	LDTA150	1/2" : 14x18	15-150	---	11-110	625	1.3
LDTE200	LDTP200	LDTS200	LDTA200	1/2" : 14x18	20-200	---	14-147	625	1.3
LDTE250	LDTP250	LDTS250	LDTA250	1/2" : 14x18	25-250	---	18.4-184	625	1.3
LDTE300	LDTP300	LDTS300	LDTA300	1/2" : 14x18	30-300	---	22-220	625	1.3
LDTE340	LDTP340	LDTS340	LDTA340	1/2" : 14x18	34-340	---	25-250	625	1.3
		LTDS600	LDTA600	3/4"	60-600	---	44-440	1000	3.92
		LTDS800	LDTA800	3/4"	80-800	---	59-590	1000	3.92
		LTDS1000	LDTA1000	3/4"	100-1000	---	73-737	1000	3.92

 733/10 - Herramientas acoplables de boca en estrella OPEN-RING



+ Ampliar

→ Dimensiones del dibujo

Código	 mm	 mm	b mm	h mm	W mm	S mm	 g	Unidad
58231010	10	9x12	21,5	11	7,1	17,5	57	
58231011	11	9x12	22,5	11	8,6	17,5	55	
58231012	12	9x12	24,5	12	9	17,5	59	
58231013	13	9x12	26	12	10	17,5	55	
58231014	14	9x12	27	13	11	17,5	60	
58231016	16	9x12	30,5	13	13	17,5	65	
58231017	17	9x12	31,5	13	14	17,5	64	
58231018	18	9x12	33	15	14,8	17,5	74	
58231019	19	9x12	34	15	15,8	17,5	80	
58231021	21	9x12	38,5	15	16,2	20*	88	
58231022	22	9x12	39,5	15	17	20*	92	
58231024	24	9x12	40	15	18	20*	75	

Jean Louis MENEGON

Représentant et Conseiller

Région Sud Ouest

Tel : 06 76 08 96 83

Email: jlouismenegon@aol.com

www.menegon-metrologie.com

Visiter le site web :

www.menegon-metrologie.com